



NA 6700 Grout Rescue Grout Colorant and Sealer

GOOD	BETTER	BEST
------	--------	------

PRODUCT DESCRIPTION

NA 6700 Grout Rescue is a ready-to-use, non-flammable, water-based, polymer-modified colorant and sealer for grout joints.

USES

Apply NA 6700 Grout Rescue over existing sanded, unsanded or epoxy grout joints. NA 6700 Grout Rescue can be used on interior/exterior residential and commercial floors and walls. It is ideal for reviving the color of existing grout joints or for changing the color of grout joints, without the inconvenience of replacing the grout.

LIMITATIONS

- For new installations, grout should cure at least 48 hours before being coated with NA 6700 Grout Rescue.
- Do not clean with solvent-based cleaners after NA 6700 Grout Rescue has been applied.
- Do not use on submerged installations such as pools, fountains, water features or areas subject to water pressure from under or behind an installation.
- Do not use on installations that require chemical resistance.
- Porous tile or stone may require sealing before NA 6700 Grout Rescue is applied.
- Apply only when substrate and ambient temperature are between 50°F and 95°F (10°C and 35°C).

SURFACE PREPARATION

1. Grout should be clean and free of dust, dirt, oil, grease, paint, curing agents, concrete sealers, loosely bonded toppings or particles, and any other substance or condition that may prevent or reduce adhesion.
2. Refer to North American's Surface Preparation Requirements document for tile and stone installation systems at www.na-adhesives.com.
3. Ensure materials and jobsite are between 50°F and 95°F (10°C and 35°C).
4. To prevent staining, some tiles with high water absorption such as marble or granite may require an appropriate sealer before applying NA 6700 Grout Rescue. Test NA 6700 Grout Rescue on a separate area for suitability before use.

MIXING

1. Shake well before using.
2. If two or more bottles of the same color are to be used, blend the liquids together to ensure color consistency.

APPLICATION

1. Apply NA 6700 Grout Rescue on grout joints with a small brush, brush applicator or roller applicator.
2. Work the colorant into the grout joint with a back-and-forth motion to penetrate the grout and ensure a proper bond.

TECHNICAL QUICK REFERENCE

Product characteristics at 73°F (23°C) and 50% relative humidity

Colors	NA 6700 Grout Rescue is available in select colors. Refer to grout chip kits or color cards as the color standard.
Cleanup	With clean water while fresh
Dry time	30 minutes to 2 hours
Shelf life	2 years when stored in original sealed container at room temperature in a dry, heated area. Protect from moisture, freezing and excessive heat.
Packaging	Plastic dispenser bottle: 8 U.S. oz. (237 mL)

INSTALLATION COVERAGE per 8 U.S. oz. (237 mL)

Tile Size	Grout Joint Width	Installation Coverage*
2" x 2" (5 x 5 cm)	3/16" (4,5 mm)	85 sq. ft. (7,90 m ²)
4" x 4" (10 x 10 cm)	1/8" (3 mm)	200 sq. ft. (18,6 m ²)
	1/4" (6 mm)	80 sq. ft. (7,43 m ²)
6" x 6" (15 x 15 cm)	3/8" (10 mm)	55 sq. ft. (5,11 m ²)
	1/4" (6 mm)	95 sq. ft. (8,83 m ²)
12" x 12" (30 x 30 cm)	3/8" (10 mm)	70 sq. ft. (6,50 m ²)
	1/4" (6 mm)	125 sq. ft. (11,6 m ²)
18" x 18" (45 x 45 cm)	3/8" (10 mm)	95 sq. ft. (8,83 m ²)
	1/2" (12 mm)	63 sq. ft. (5,85 m ²)
18" x 18" (45 x 45 cm)	1/8" (3 mm)	255 sq. ft. (23,7 m ²)
	1/4" (6 mm)	220 sq. ft. (20,4 m ²)
	3/8" (10 mm)	165 sq. ft. (15,3 m ²)

* Installation coverage depends on tile size, grout joint width, grout porosity and application method.

HEALTH AND SAFETY

Consult the Material Safety Data Sheet (MSDS) for safe-handling instructions.

3. If the grout joint is a dark color and NA 6700 Grout Rescue is a lighter color, more than one coat may be required. Allow 1 to 2 hours between coats.
4. After application, let NA 6700 Grout Rescue dry 30 to 60 minutes, and then lightly mist surface with water.
5. Let misted water stand 5 minutes. Then use nylon scrubpad to remove excess colorant.

CLEANUP

- Clean hands and tools with water while NA 6700 Grout Rescue is fresh.

PROTECTION

- Protect from freezing in transit and in storage.
- Provide dry, heated storage on site. Deliver materials at least 24 hours before tilework begins.
- Protect from traffic for 2 hours, and from water for 24 hours.
- To allow for full cure, avoid scrubbing or excessive cleaning of grout joint for 20 days after application.

NA 6700

MAINTENANCE

- When using *NA 6700 Grout Rescue*, sealing of grout joints is not required.

IMPORTANT NOTICE

Before using, user shall determine the suitability of the product for its intended use and user alone assumes all risks and liability whatsoever in connection therewith. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.**

For the most current product data, visit www.na-adhesives.com.



North American
ADHESIVES®

MAPEI® Corporation
1144 East Newport Center Drive
Deerfield Beach, FL 33442
Customer Service: 1-800-747-2722
Technical Services: 1-800-637-7753
www.na-adhesives.com

PR 6204 6700D_G11Evp
© 2011 MAPEI Corporation. All Rights Reserved.
Printed in the USA.