



Urethane Adhesive Cleaner

GOOD	BETTER	BEST
------	--------	------

PRODUCT DESCRIPTION

A ready-to-use urethane adhesive cleaner designed to effectively remove urethane adhesive from the surface of prefinished wood flooring. NA 8550 is low-odor, nonflammable, pH-neutral and biodegradable. Safe for use on most types of prefinished wood flooring including parquet, engineered, solid and bamboo, it also removes urethane adhesive from trowels and tools. Simple to use, it is conveniently packaged in both quarts and pre-moistened towelettes.

USES

- For removing fresh, wet NA 8500 adhesive from prefinished wood flooring including parquet, engineered, solid and bamboo
- For cleaning fresh, wet NA 8500 adhesive from trowels and tools
- For softening semi-cured NA 8500 adhesive to aid in the removal
- For cleaning fresh, wet or semi-cured NA 1300 from tools, trowels or residue on surfaces

Note: NA 8500 adhesive is very difficult to remove once dry and cured. During the installation of glue-down wood flooring, make every effort to prevent adhesive from getting on the flooring surface. For best results, remove adhesive smudges and drops immediately during installation.

LIMITATIONS

- Do not use as a hand-cleaner. Use gloves to protect skin.
- Protect carpeting, wood cabinets, painted surfaces and other finished surfaces.
- Avoid spilling excess amounts of NA 8550, which may seep in between wood flooring and weaken the bond of the urethane adhesive. Keep an absorbent product handy (paper towels, sawdust, kitty litter, etc.) to absorb spills.
- Do not leave NA 8550 on the surface of the wood flooring for longer than 60 minutes.
- Thoroughly rinse and dry the area of application after use.
- Avoid using metal blades or other sharp objects when removing the adhesive, as this can permanently damage the surface of the finished floor.
- Test for compatibility with flooring in a small inconspicuous area before using.

TECHNICAL QUICK REFERENCE

Product characteristics at 73°F (23°C) and 50% relative humidity	
Application temperature	From 50°F to 90°F (10°C to 32°C)
Odor	Slight odor
pH	Not applicable
Volatile organic compounds (VOCs)	575 g/L VOC – per California's South Coast Air Quality Management District, Rule 1168
Flash point	205°F (96°C)
Freeze/thaw stability	Protect from freezing
Color	Light yellow to clear liquid
Shelf life	1 year when stored in original unopened container at room temperature (73°F [23°C]) in a dry area
Packaging	Bottle: 1 U.S. qt. (946 mL); Pop-up dispenser (30 wipes); Pop-up dispenser (60 wipes)

HEALTH AND SAFETY

Consult the Material Safety Data Sheet (MSDS) for safe-handling instructions.

APPLICATION

Before using, test NA 8550 on a spare piece of uninstalled flooring to verify that it will not damage the finish of the wood flooring. The wood flooring's quality and durability in finish as well as its resistance to damage from chemical cleaners and glues will vary greatly from one manufacturer to another. Regardless of the brand of flooring, always perform a compatibility test before using.

1. For removing fresh, wet NA 8500 or NA 1300 from prefinished wood flooring during the installation of glue-down wood flooring
 - 1.1 Dampen a nonabrasive, clean white towel or cloth with NA 8550, or use a pre-moistened NA 8550 towelette.
 - 1.2 Place the towel/cloth or towelette on fresh, wet adhesive and allow to remain for about 5 to 10 minutes.
 - 1.3 Remove adhesive with the soft, clean white towel or pre-moistened towelette.
 - 1.4 Rinse the area completely with clean soapy water.
 - 1.5 Dry the area with another soft, clean white towel.
2. For removing NA 8500 or NA 1300 from trowels and tools
 - 2.1 Soak trowels and tools in NA 8550.
 - 2.2 Scrape and/or wipe off softened adhesive.
 - 2.3 Rinse tools with clean soapy water and allow to dry.

NA 8550

IMPORTANT NOTICE

Before using, user shall determine the suitability of the product for its intended use and user alone assumes all risks and liability whatsoever in connection therewith. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.**

For the most current product data, visit www.na-adhesives.com.



North American
ADHESIVES®

MAPEI® Corporation
1144 East Newport Center Drive
Deerfield Beach, FL 33442
Customer Service and
Technical Services: 1-800-637-7753
www.na-adhesives.com

PR 5657 8550D_B09vp
© 2009 MAPEI Corporation. All Rights Reserved.
Printed in the USA.