

Material Safety Data Sheet

Material Name: NA 8500 Solid Wood Flooring Adhesive

ID: SAH00024

*** Section 1 - Chemical Product and Company Identification ***

Material Name: NA 8500 Solid Wood Flooring Adhesive

Product Use

Flooring Adhesive

Manufacturer Information

USA and Puerto Rico

North American Adhesives

1144 East Newport Center Drive

Deerfield Beach, FL 33442

Phone: 1-954-246-8888

Canada

North American Adhesives

2900 Francis-Hughes Avenue

Laval, QC H7L 3J5

Phone: 1-450-662-1212

IN THE EVENT OF A CHEMICAL EMERGENCY INVOLVING A SPILL, LEAK, FIRE, EXPLOSION, EXPOSURE OR ACCIDENT, CONTACT THE FOLLOWING NUMBERS:

Emergency 24 hour numbers:

(USA) CHEMTREC 1-800-424-9300

(Canada) CANUTEC 1-631-996-6666

*** Section 2 - Hazards Identification ***

Emergency Overview

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication). This product is irritating to the eyes. This product may cause sensitization by inhalation and skin contact.

Hazard Statements

CAUTION! Irritating to eyes. May cause sensitization by inhalation and skin contact. Wear suitable gloves, eye/face protection, and respiratory protection. Keep out of the reach of children.

Potential Health Effects: Eyes

This product is irritating to the eyes.

Potential Health Effects: Skin

This product may cause irritation to the skin. Prolonged contact with this product may cause allergic skin sensitization reactions.

Potential Health Effects: Ingestion

Ingestion of this product may cause nausea, vomiting and diarrhea.

Potential Health Effects: Inhalation

This product may cause irritation to the respiratory system. This product may cause sensitization by inhalation.

Medical Conditions Aggravated by Exposure

Hypersensitivity to product, allergies, and skin or respiratory disorders

Potential Environmental Effects

None identified.

HMIS Ratings: Health: 1 Fire: 0 Reactivity: 0 Pers. Prot.: Safety glasses and gloves

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

*** Section 3 - Composition / Information on Ingredients ***

CAS #	Component	Percent
68083-75-0	Urethane Polymer	10-30
1305-78-8	Calcium oxide	7-13
64742-46-7	Petroleum distillates, hydrotreated middle	7-13
101-68-8	Methylene bisphenol isocyanate (MDI)	1-5
6422-86-2	1,4-Benzenedicarboxylic acid, bis(2-ethylhexyl) ester	1-5
120-55-8	Diethylene glycol dibenzoate	0.5-1.5

Material Safety Data Sheet

Material Name: NA 8500 Solid Wood Flooring Adhesive

ID: SAH00024

Component Related Regulatory Information

This product may be regulated, have exposure limits or other information identified as the following: Benzene compounds.

Component Information/Information on Non-Hazardous Components

*** Section 4 - First Aid Measures ***

First Aid: Eyes

In case of contact, immediately flush eyes with large amounts of water, continuing to flush for 15 minutes. If irritation persists get medical attention.

First Aid: Skin

For skin contact, flush with large amounts of water. If irritation persists, get medical attention.

First Aid: Ingestion

For ingestion, flush out mouth with water. If ingestion of a large amount does occur, seek medical attention. Do not induce vomiting.

First Aid: Inhalation

If inhaled, immediately remove the affected person to fresh air. If the affected person is not breathing, apply artificial respiration. If symptoms persist, get medical attention.

First Aid: Notes to Physician

Provide general supportive measures and treat symptomatically.

*** Section 5 - Fire Fighting Measures ***

General Fire Hazards

See Section 9 for Flammability Properties.

This product is an aqueous mixture which will not burn. If evaporated to dryness, the solid residue may pose a moderate fire hazard.

Hazardous Combustion Products

Irritating and toxic gases or fumes may be released during a fire. Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Extinguishing Media

Dry chemical (preferred), foam, water.

Fire Fighting Equipment/Instructions

Firefighters should wear full protective gear.

NFPA Ratings: Health: 1 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

*** Section 6 - Accidental Release Measures ***

Personal Precautions

Wear appropriate protective equipment and clothing during clean-up.

Containment Procedures

Dike the spilled material, where this is possible. Absorb with inert absorbent such as dry clay, sand or diatomaceous earth, commercial sorbents, or recover using pumps. Scoop up used absorbent into drums or other appropriate container.

Environmental Precautions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

Clean-Up Procedures

Attempt to reclaim the free product, if this is possible. Shovel the material into waste container. Thoroughly wash the area with water after a spill or leak clean-up. Keep out of the reach of children.

Evacuation Procedures

None identified.

Special Procedures

Regulations vary. Consult local authorities before disposal.

Material Safety Data Sheet

Material Name: NA 8500 Solid Wood Flooring Adhesive

ID: SAH00024

*** Section 7 - Handling and Storage ***

Handling Procedures

Avoid getting this material into contact with your skin and eyes. Avoid breathing vapors or mists of this product. Wash hands after handling and before eating. Keep out of the reach of children.

Storage Procedures

Store in a cool, dry, well-ventilated area. Store at ambient temperature and atmospheric pressure. Keep out of sun.

*** Section 8 - Exposure Controls / Personal Protection ***

A: Component Exposure Limits

Calcium oxide (1305-78-8)

ACGIH: 2 mg/m³ TWA

OSHA 5 mg/m³ TWA

(Final):

OSHA 5 mg/m³ TWA (not in effect as a result of reconsideration)

(Vacated):

NIOSH: 2 mg/m³ TWA

Alberta: 2 mg/m³ TWA

British 2 mg/m³ TWA

Columbia:

Manitoba: 2 mg/m³ TWA

New 2 mg/m³ TWA

Brunswick:

NW 2 mg/m³ TWA

Territories: 4 mg/m³ STEL

Nova Scotia: 2 mg/m³ TWA

Nunavut: 2 mg/m³ TWA

4 mg/m³ STEL

Ontario: 2 mg/m³ TWAEV

Quebec: 2 mg/m³ TWAEV

Saskatchewan 2 mg/m³ TWA

n: 4 mg/m³ STEL

Yukon: 2 mg/m³ TWA

4 mg/m³ STEL

Material Safety Data Sheet

Material Name: NA 8500 Solid Wood Flooring Adhesive

ID: SAH00024

Methylene bisphenol isocyanate (MDI) (101-68-8)

ACGIH: 0.005 ppm TWA
OSHA 0.02 ppm Ceiling; 0.2 mg/m³ Ceiling
(Final):
OSHA 0.02 ppm Ceiling; 0.2 mg/m³ Ceiling
(Vacated):
NIOSH: 0.005 ppm TWA; 0.05 mg/m³ TWA
0.020 ppm Ceiling (10 min); 0.2 mg/m³ Ceiling (10 min)
Alberta: 0.005 ppm TWA; 0.051 mg/m³ TWA
British
Sensitizer
Columbia: 0.005 ppm TWA
0.01 ppm Ceiling
Skin notation
Manitoba: 0.005 ppm TWA
New
0.005 ppm TWA; 0.051 mg/m³ TWA
Brunswick:
NW 0.02 ppm Ceiling; 0.2 mg/m³ Ceiling
Territories:
Nova Scotia: 0.005 ppm TWA
Nunavut: 0.02 ppm Ceiling; 0.2 mg/m³ Ceiling
Ontario: 0.005 ppm TWAEV; 0.2 µmol/m³ TWAEV; 0.02 ppm CEV; 0.8 µmol/m³ CEV
0.005 ppm TWAEV (designated substance regulation); 0.2 µmol/m³ TWAEV
(designated substance regulation)
0.02 ppm CEV (designated substances regulation); 0.8 µmol/m³ CEV (designated
substances regulation)
Quebec: 0.005 ppm TWAEV; 0.051 mg/m³ TWAEV
Saskatchewan 0.005 ppm TWA
n: 0.015 ppm STEL
Yukon: 0.02 ppm Ceiling; 0.2 mg/m³ Ceiling

Engineering Controls

Use general ventilation.

PERSONAL PROTECTIVE EQUIPMENT

Personal Protective Equipment: Eyes/Face

Wear safety glasses with side shields.

Personal Protective Equipment: Skin

The use of nitrile-latex gloves is recommended.

Personal Protective Equipment: Respiratory

Not normally needed. If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

Personal Protective Equipment: General

Laundry contaminated clothing before reuse. Use good industrial hygiene practices in handling this material.

*** Section 9 - Physical & Chemical Properties ***

Material Safety Data Sheet

Material Name: NA 8500 Solid Wood Flooring Adhesive

ID: SAH00024

Appearance:	Beige paste	Odor:	Slight latex odor
Physical State:	Paste	pH:	8.0 - 10.0
Vapor Pressure:	N/A	Vapor Density:	1.1 - 1.2
Boiling Point:	>212° F (>100° C)	Melting Point:	N/A
Solubility (H2O):	Same as water	Specific Gravity:	1.3 - 1.6
Evaporation Rate:	N/A	VOC:	44 g/L
Octanol/H2O Coeff.:	N/A	Flash Point:	N/A
Flash Point Method:	N/A	Upper Flammability Limit (UFL):	N/A
Lower Flammability Limit (LFL):	N/A	Burning Rate:	N/A
Auto Ignition:	N/A		

Physical Properties: Additional Information

The data provided in this section is to be used for product safety handling purposes. Please refer to Product Data Sheets, Certificates of Conformity or Certificates of Analysis for chemical and physical data for determinations of quality and for formulation purposes.

* * * Section 10 - Chemical Stability & Reactivity Information * * *

Chemical Stability

Stable under normal conditions.

Chemical Stability: Conditions to Avoid

Do not freeze.

Incompatibility

This product may react with strong acids, bases and oxidizing agents.

Hazardous Decomposition

Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition. Upon decomposition, this product may emit fumes of carbon monoxide, carbon dioxide, oxides of nitrogen, and other organic compounds.

Possibility of Hazardous Reactions

Will not occur.

* * * Section 11 - Toxicological Information * * *

Acute Dose Effects

A: General Product Information

No information available for the product.

B: Component Analysis - LD50/LC50

Calcium oxide (1305-78-8)

Oral LD50 Rat: 500 mg/kg

Petroleum distillates, hydrotreated middle (64742-46-7)

Inhalation LC50 Rat: 4.6 mg/L/4H; Oral LD50 Rat: 7400 mg/kg; Dermal LD50 Rabbit: >2000 mg/kg

Methylene bisphenol isocyanate (MDI) (101-68-8)

Oral LD50 Rat: 9200 mg/kg

Diethylene glycol dibenzoate (120-55-8)

Oral LD50 Rat: 2830 mg/kg; Dermal LD50 Rabbit: 20 mL/kg

Carcinogenicity

A: General Product Information

No information available for the product.

Material Safety Data Sheet

Material Name: NA 8500 Solid Wood Flooring Adhesive

ID: SAH00024

B: Component Carcinogenicity

Methylene bisphenol isocyanate (MDI) (101-68-8)

IARC: Monograph 71 [1999], Supplement 7 [1987], Monograph 19 [1979] (Group 3 (not classifiable))

Sensitization

No information available for the product.

*** Section 12 - Ecological Information ***

Ecotoxicity

A: General Product Information

No information available for the product.

B: Component Analysis - Ecotoxicity - Aquatic Toxicity

Calcium oxide (1305-78-8)

Test & Species

	Conditions
96 Hr LC50 Cyprinus carpio	1070 mg/L [static]
96 Hr LC50 Cyprinus carpio	1070 mg/L

Conditions

Petroleum distillates, hydrotreated middle (64742-46-7)

Test & Species

	Conditions
96 Hr LC50 Pimephales promelas	35 mg/L [flow-through]

Conditions

*** Section 13 - Disposal Considerations ***

US EPA Waste Number & Descriptions

A: General Product Information

No additional information available.

B: Component Waste Numbers

No EPA Waste Numbers are applicable for this product's components.

Disposal Instructions

Waste must be handled in accordance with all federal, state, provincial, and local regulations. Consult authorities before disposal.

See Section 7 for Handling Procedures. See Section 8 for Personal Protective Equipment recommendations.

*** Section 14 - Transportation Information ***

International Transportation Regulations

Not regulated as dangerous goods.

*** Section 15 - Regulatory Information ***

US Federal Regulations

A: General Product Information

All components are on the U.S. EPA TSCA Inventory List. All components of this product are included, or are exempt from inclusion, in the Canadian Domestic Substance List unless otherwise noted.

B: Component Analysis

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65) and/or CERCLA (40 CFR 302.4).

Methylene bisphenol isocyanate (MDI) (101-68-8)

SARA 313: 1.0 % de minimis concentration (listed under Chemical Category N120, Diisocyanates)
CERCLA: 5000 lb final RQ; 2270 kg final RQ

State Regulations

A: General Product Information

Other state regulations may apply. Check individual state requirements.

Material Safety Data Sheet

Material Name: NA 8500 Solid Wood Flooring Adhesive

ID: SAH00024

B: Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA	RI
Calcium oxide	1305-78-8	Yes	Yes	Yes	Yes	Yes	Yes
Methylene bisphenol isocyanate (MDI)	101-68-8	Yes	Yes	Yes	Yes	Yes	Yes

Canadian WHMIS Information

A: General Product Information

Not regulated

B: Component Analysis - WHMIS IDL

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

Component	CAS #	Minimum Concentration
Calcium oxide	1305-78-8	1 %
Methylene bisphenol isocyanate (MDI)	101-68-8	0.1 %

Additional Regulatory Information

A: General Product Information

Supplier(s) of proprietary component(s) state that these components are contained on the TSCA inventory.

B: Component Analysis - Inventory

Component	CAS #	TSCA	CAN	EEC
1,2-Propanediol, polymer with 1,1'-methylenebis[4-isocyanatobenzene], methyloxirane and oxirane	68083-75-0	Yes	DSL	No
Calcium oxide	1305-78-8	Yes	DSL	EINECS
Petroleum distillates, hydrotreated middle	64742-46-7	Yes	DSL	EINECS
Methylene bisphenol isocyanate (MDI)	101-68-8	Yes	DSL	EINECS
1,4-Benzenedicarboxylic acid, bis(2-ethylhexyl) ester	6422-86-2	Yes	DSL	EINECS
Diethylene glycol dibenzoate	120-55-8	Yes	DSL	EINECS

*** Section 16 - Other Information ***

Reference Version (internal)

02

Other Information

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use.

Key/Legend

NA = Not available or Not Applicable. ACGIH = American Conference of Governmental Industrial Hygienists. NFPA = National Fire Protection Association. EPA = Environmental Protection Agency; TSCA = Toxic Substance Control Act; ACGIH = American Conference of Governmental Industrial Hygienists; IARC = International Agency for Research on Cancer; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration., NJTSR = New Jersey Trade Secret Registry.

End of Sheet SAH00024