

NA 2600 & NA 2700



North American
ADHESIVES®

Premixed, Sanded and Unsanded Adhesive and Grout



GOOD	BETTER	BEST
------	--------	------

PRODUCT DESCRIPTION

Ready-to-use, no-mix, all-in-one adhesives and grouts

USES

- For indoor use only with ceramic, quarry, porcelain and impervious mosaic tile
- For ceramic tile installations on floors (light-duty residential traffic only), walls and countertops
- For shower, tub and bath surrounds where service requirements do not exceed ANSI A136.1, Type 1 industry standards

SUBSTRATE REQUIREMENTS

- The substrate must be in accordance with ANSI A108.5 current standards and recommendations.
- Substrate must be structurally sound, dry, and free of any substance or coatings that might weaken mortar bond to substrate. Any foreign substance must be mechanically removed.

SUITABLE SUBSTRATES (properly prepared)

- Cured concrete
- Gypsum wallboard
- Cementitious backer units
- Exterior-grade Douglas fir plywood conforming to U.S. Product Standard PS 1.83 and A.P.A. Classification Group 1, CC-plugged or better or CSA-0121 Standard Exterior Select or (SEL-TF) according to COFI classification

LIMITATIONS

- Do not use outdoors.
- Do not use on shower floors.
- Do not apply over particleboard, Masonite, Luan, gypsum floor-patching compounds, metal or similar dimensionally unstable substrates.
- Do not use at temperatures below 50°F (10°C).
- Do not use to install marble, granite or their agglomerates.
- Do not use for setting bathroom fixtures, grab bars or over metal surfaces.
- NA 2600 and NA 2700 are not recommended for outdoor or complete immersion tilework.

MIXING


NA 2600 and NA 2700 are ready-to-use. No mixing is required.

APPROXIMATE COVERAGES*

As a mortar, per 1 U.S. gal. (3,79 L)

Typical trowels

3/16" x 3/16"	24 to 28 sq. ft.
(4,5 x 4,5 mm)	(2,23 to 2,60 m ²)
1/4" x 1/4" x 1/4"	20 to 24 sq. ft.
(6 x 6 x 6 mm)	(1,86 to 2,23 m ²)



As a grout, per 1 U.S. gal. (3,79 L)

Tile size	Joint width	
	1/8" (3 mm)	3/16" (4,5 mm)
4" x 4" x 1/4" (10 cm x 10 cm x 6 mm)	90 to 100 sq. ft. (8,36 to 9,29 m ²)	45 to 50 sq. ft. (4,18 to 4,65 m ²)
6" x 6" x 3/16" (15 cm x 15 cm x 4,5 mm)	150 to 160 sq. ft. (13,9 to 14,9 m ²)	75 to 80 sq. ft. (6,97 to 7,43 m ²)

* Coverages are for estimating only. Actual coverages may vary according to substrate conditions, trowel used and setting practices

HEALTH AND SAFETY

Consult the Material Safety Data Sheet (MSDS) for safe-handling instructions.

APPLICATION (as a mortar)

1. Use a typical notched trowel (see chart) with sufficient depth to achieve a transfer of at least 80% adhesive to the back of the tile.
2. Spread the adhesive on the substrate. Do not spread more than can be applied within 30 minutes.
3. Place tiles firmly into the fresh adhesive with a slight twisting motion to ensure a positive bond. If skinning occurs, remove the dry adhesive and replace with fresh adhesive before applying more tiles.
4. Make alignments or adjustments immediately (do not exceed 45 minutes).

APPLICATION (as a grout)

1. Let adhesive dry completely before grouting.
2. Walls: Grouting may be done the day following installation.
3. Floors: Grouting may generally be done after 24 to 48 hours, depending on the tiles used.

CLEANING

Clean surfaces, tools and hands with fresh water while adhesive is wet. If adhesive has dried, use mineral spirits.

PROTECTION

Protect from freezing in transit and storage. If material is frozen, do not stir it until it has returned to room temperature.

NA 2600 & NA 2700

IMPORTANT NOTICE

Before using, user shall determine the suitability of the product for its intended use and user alone assumes all risks and liability whatsoever in connection therewith. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.**

For the most current product data, visit www.na-adhesives.com.



North American
ADHESIVES®

MAPEI® Corporation
1144 East Newport Center Drive
Deerfield Beach, FL 33442
Customer Service: 1-800-637-7753
Technical Services: 1-800-992-6273
www.na-adhesives.com

PR 5393 2600-2700D_A08vp
© 2008 MAPEI Corporation. All Rights Reserved.
Printed in the USA.