



North American
ADHESIVES®

NA 6700

Grout Rescue™

Grout Colorant and Sealer



PRODUCT DESCRIPTION

NA 6700 Grout Rescue is a ready-to-use, nonflammable, water-based, polymer-modified colorant and sealer for grout joints.

USES

Apply *NA 6700 Grout Rescue* over existing sanded, unsanded and epoxy grout joints. *NA 6700 Grout Rescue* can be used on interior/exterior residential and commercial floors and walls. It is ideal for reviving the color of existing grout joints or for changing the color of grout joints, without the inconvenience of replacing the grout.

LIMITATIONS

- New installations of grout should cure for at least 48 hours before being coated with *NA 6700 Grout Rescue*.
- Do not clean grout joints with solvent-based cleaners after *NA 6700 Grout Rescue* has been applied.
- Do not use on submerged installations such as pools, fountains, water features or areas subject to water pressure from under or behind an installation.
- Do not use on installations that require chemical resistance.
- Do not mix with other ingredients.
- Porous tile or stone may require sealing before *NA 6700 Grout Rescue* is applied.
- Apply only when substrate and ambient temperature are between 50°F and 95°F (10°C and 35°C).

SUBSTRATE REQUIREMENTS

- Grout should be clean and free of dust, dirt, oil, grease, paint, curing agents, concrete sealers, loosely bonded toppings and particles, and any other substance and condition that may prevent or reduce adhesion.

Refer to North American Adhesives' "Surface Preparation Requirements" document for tile and stone installation systems at www.na-adhesives.com.

MIXING

Consult the Safety Data Sheet for safe-handling instructions.

- Shake well before using.
- If two or more bottles of the same color are to be used, blend the liquids together to ensure color consistency.

APPLICATION

- Ensure that materials as well as substrate and ambient temperatures are at between 50°F and 95°F (10°C and 35°C).
 - To prevent staining, some tiles with high water absorption such as marble or granite may require an appropriate sealer before applying *NA 6700 Grout Rescue*. Test *NA 6700 Grout Rescue* on a separate area for suitability before use.
1. Apply *NA 6700 Grout Rescue* on grout joints with a small brush or brush applicator.
 2. Work the colorant into the grout joint with a back-and-forth motion to penetrate the grout and ensure a proper bond.
 3. If grout joints are a dark color and *NA 6700 Grout Rescue* is a lighter color, more than one coat may be required. Allow 1 to 2 hours between coats.
 4. Let *NA 6700 Grout Rescue* dry for 30 to 60 minutes.
 5. Lightly mist the surface with water and let the water stand for 5 minutes. Then use a nylon scrubpad to remove excess colorant.

CLEANUP

- Clean hands and tools with water while *NA 6700 Grout Rescue* is fresh.

PROTECTION

- Protect *NA 6700 Grout Rescue* from moisture, freezing and excessive heat in transit and in storage.
- Provide dry, heated storage on site. Deliver materials at least 24 hours before tilework begins.
- Protect installation from traffic for 2 hours, and from water for 24 hours.

NA 6700 Grout Rescue™

- To allow for full cure, avoid scrubbing or excessive cleaning of grout joints for 20 days after application of *NA 6700 Grout Rescue*.

MAINTENANCE

- When *NA 6700 Grout Rescue* is used, sealing of grout joints is not required.

Product Characteristics	
at 73°F (23°C) and 50% relative humidity	
Colors	<i>NA 6700 Grout Rescue</i> is available in select colors. Refer to grout chip kits or color cards as the color standard.
Shelf life	2 years when stored in original sealed container at room temperature in a dry area
Drying time	30 minutes to 2 hours
Packaging	Plastic dispenser bottle: 8 U.S. oz. (237 mL)

Approximate Coverage* per 8 U.S. oz. (237 mL)
50 to 300 sq. ft. (4,65 to 27,9 m ²)

* Coverage rate will vary based on application method, tile size, joint width and porosity.



MAPEI® Corporation
1144 East Newport Center Drive
Deerfield Beach, FL 33442
Customer Service: 1-800-747-2722
Technical Services: 1-800-637-7753

© 2015 MAPEI Corporation
All Rights Reserved.
Printed in the USA.
PR: 6204 MKT: 15-2150
Edition Date: November 23, 2015

Refer to the Safety Data Sheet for specific data related to health and safety as well as product handling. For the most current product data and warranty information, visit www.na-adhesives.com.



Statement of Responsibility

Before using, user shall determine the suitability of the product for its intended use and user alone assumes all risks and liability whatsoever in connection therewith. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.**